

Project Location & Description

- Constructed in 1913
- White Salmon River in Klickitat and Skamania Counties in southern Washington
- 3.3 miles upstream from the confluence with the Columbia River
- Only man-made impoundment between Mt. Adams and the Columbia River
- 14.7 megawatt facility this would power 6,850 households on average
- Run-of-the-river project



Looking Downstream at Dam Site

1239 Coffer-dam

Looking Upstream from Crest of Dam

1239 443 Upstream from Crest of Dam. 3-1

Looking Downstream Through Dam Site



ite.8-20-12

Upstream Face of Dam

1239 Upstream-Face of Dam, 3-15-13

1999 Settlement Agreement Components

- PacifiCorp will complete actions to remove features of the project
- PacifiCorp's financial obligation towards removal is capped at \$17,150,000 (1999 \$; final \$ will be escalated to account for inflation)
- \$1,000,000 of cap shall go to the Yakama Nation for "enhancement, supplementation, and conservation of fishery resources"



Parties To The Settlement Agreement

PacifiCorp American River American Whitewater Affiliation Columbia Gorge Audubon Society **Columbia Gorge Coalition** Federation of Fly Fishers Friends of the Earth Washington Department of Fish and Wildlife Washington Wilderness Coalition Columbia River United Friends of the Columbia Gorge Trout Unlimited

Columbia River Intertribal Fish Commission Yakama Nation National Marine Fisheries Service Friends of the White Salmon River **U.S.** Forest Service U. S. Department of the Interior Washington Department of Ecology **Rivers Council of Washington** Washington Trout The Mountaineers The Sierra Club



Remaining milestones and expected schedule

July 2008Department of Ecology releases SEPAEnvironmental Impact Statement Amendment

August 2008Department of Ecology issues Clean Water Act401 certificate

September 2008 U.S. Army Corps of Engineers issues 404 Permit

October 2008 FERC issues Surrender Order

October 2009 Decommissioning begins



How will PacifiCorp remove the Condit Hydroelectric Project?




Project Removal Process

- Project removal will begin in October 2009
- All project components (dam, flowline, penstocks, surge tank and cofferdams) will be removed except for the powerhouse
- Reservoir will be drained in approximately six hours via a 12'x18' tunnel drilled through the base of the dam
- If possible and economical, removed material will be recycled
- Best management practices will be utilized throughout the entire dam removal and restoration processes
- Short-term impacts will be mitigated by the long-term benefits of Condit's removal



Dam Removal





Upstream Face of Dam

1239 Upstream-Face of Dam, 3-15-13

Pre Removal Actions

- Collection and transport of Adult Fall Chinook upstream of reservoir
 - Purposes:
 - Initiate natural spawning above project area
 - Spawning gravel prep
 - Provide marine-derived nutrients
 - Natural production
- Western Pond Turtle survey (2004)
- Noxious Weed survey (2007)



Removal Effects & Mitigation

- 2.3 million cubic yards of sediment have built up behind the dam since 1913
- Based on studies, the majority of the sediment will be transported downstream the first year
- Sediment assessment to be conducted immediately after the reservoir is drained
- Sediment slope stabilization an important step in "jump starting" area restoration



Site Restoration

- Revegetation is anticipated in the first growing season following removal using native seeding
- A number of plans are in preparation to restore the project area following removal. Some of them are:
 - Reservoir, Uplands and Disturbed Area Revegetation, Monitoring and Noxious Weed Control Plan
 - Wetland Monitoring and Mitigation Plan
 - Sediment and Soil Erosion Control Plan
 - Sediment Management, Stabilization, and Assessment Plan
 - Canyon Woody Debris Management Plan
 - Aquatic Resources Protection Plan
- Approximately 15 miles of new habitat will be opened to salmon and steelhead









